

### Specifications

SERIES / 4001 - 4002 - 4003 - 4213 - 4904

WINSUN - SUNSCREEN - POLSYESTER / PVC

Composition

30% Polyester, 70% PVC

Width(cm)

200 / 250 / 300

Openness Factor(%)

5%

Thickness(mm)

0.75

Weight(g/m<sup>2</sup>)

520

Bacteria and Fugal Resistance

ASTM E2180:2007(\*)

Fire Classification

BS 5867-2 Part 2 Type B


Lead Free

16 CFR 1303 (U.S.A)

Environmental Certification

GREENGUARD Certified

*\*The amount of growing bacteria on fabric  
cfu:coloni forming units*

Color Code	Color	Openness Factor	Solar Transmisson	Solar Reflection	Light Transmission	APPLICATIONS
4001	White	5%	16%	68%	12%	
4002	Ivory	5%	15%	57%	13%	
4003	Grey	5%	11%	41%	10%	
4213	Pearl Grey	5%	10%	34%	9%	
4904	Antrasit	5%	7%	11%	8%	



**ARCHITEXTILE International B.V.**

OverSchiestraat 184, 1062 XK Amsterdam - The Netherland

Tel: +31 6 43848840

www.architextile.com • info@architextile.com